

## EW-LT19P

<i>Technical Specifications</i>		
Model name	EW-LT19 LCD Monitor	
LCD Display	19" active matrix TFT SXGA LCD	
Active Area	376.32 (H) * 301.056 (V) mm	
Dot Pitch	0.294 (H) * 0.294 (V) mm	
Contrast Ratio	600 : 1	
Brightness	250 cd/m <sup>2</sup>	
Response Time	25 ms	
Viewing Angle	Horizontal	160° +/- 10°
	Vertical	140° +/- 10°
Display Color	16.7 M colors	
PC Interface	15 Pin D-Sub, RGB, 0-0.7Vpp, RGB Analog, 75 Ohm terminated	
Display Mode	VEGA : VGA / SVGA / XGA/SXGA , MAC : 640 * 480, 800 * 600	
DVI Interface	Optional	
Max Resolution	1280 * 1024	
Horizontal Frequency	31.5 KHz ~ 60 KHz	
Vertical Frequency	56 Hz ~ 75 Hz	
OSD Controls	Contrast; Brightness, Auto adjust, Clock, Phase, H-Position, V-Position, Input...	
Power Adapter	AC Input : 100-240V ~ 1.8A, 50-60Hz DC Output : 12-17V / 4.0A, 12V, DC Input	
Operating Conditions	Temperature : 0°C ~ 50°C, Humidity : 5% ~ 90%.	
Storage Conditions	Temperature : -20°C ~ +60°C, Humidity : 5% ~ 95%.	
Speakers	2W * 2	
Plug & Play	VESA DDC2B	
Certification	CE, FCC(Doc), TUV/GS, UL	
Dimension	Set	
	Packing	
Weight	NW	6.0 Kg
	GW	7.5 Kg
Loading Quantity	20ft	720
	40ft H.Q	1440
(Optional) – TV Tuner : NTSC, Supply V-chip & Closed Caption, Function PAL, Supply Teletex Function, Supply MTS Function.		
(Optional) AV Input / S-Video Input / Audio output / Y Pb Pr Input		
<b>Note: Specifications are subjected to change without prior notice.</b>		